UC0306 说明书


材质：105g铜板
大小：60x120mm
装订：骑马钉

60mm

120mm

Product Manual

Dual Display Multifunction USB-C Hub




ENGLISH

Product Introduction

This is an alloy multifunction USB-C HUB. It mainly extends the USB-C interface of the source device to HDMI x2,RJ45, USB3.0X2, USB2.0, SD & Micro SD card reader and USB-C charging port.
Exclusive design for Macbook Pro/Air and Mac Mini.

Structure Diagram



1.HDMI 1
2.HDMI 2
3.USB3.0
4.PD3.0
5.RJ45
6.SD / Micro SD
7.USB3.0
8.USB2.0


Feature

1.HDMI 1:
4K×2K 60Hz / 3840x2160(work while source is DP1.2 or above)
2.HDMI 2:
4K×2K 60Hz / 3840x2160(work while source is DP1.4)
4K×2K 30Hz / 3840x2160(work while source is DP1.2)
3.USB 3.0
Up to 5Gbps data speed & maximum power output 5V/0.9A, backwards compatible with USB2.0/USB1.1.
4.USB-C PD3.0:
Upstream charging the source devices such as Laptop/ Notebook, Support 100W power in, charging limited to 87-96W for safety, affected by different firmware.
5.RJ45
Up to 1000Mbps, stable wired access for high-speed connectivity
6.SD/Micro SD
Data transfer rates are subject to the speed of the memory card itself and your computer's USB ports.
7.USB 3.0
Up to 5Gbps data speed & maximum power output 5V/0.9A, backwards compatible with USB2.0/USB1.1.
8.USB 2.0: Speed up to 480Mbps, 5V/0.5A@2.5W.

Remarks


1. Support MacBook's Multi-Stream
2. When two HDMI work simultaneously, when the output source is DP1.4, the resolution is up to 4K/60Hz; (When the output source is DP1.2, the resolution is up to 4K/30Hz for Mirror Mode; For Extend Mode, HDMI1 is extended to 4K/60Hz, HDMI 2 is 4K/30Hz.)

Connection




Resolution Setting for Mac

Apple logo>System Preferences>Displays



Sound Setting for Mac


Apple logo>System Preferences > Sound




Graphics Settings for Mac

1.Mirror Display

Apple logo>System Preferences >Displays






2.Extend Display


Apple logo>System Preferences >Displays





Mac Windows System display settings

Right click desktop >Display Settings




Sound Settings for win10




Mac Windows System display settings

1.Clone mode


Right click desktop >Graphics Settings >Display






2.Extended Desktop

Right click desktop >Graphics Settings >Display





Storage Conditions

Environmental Working Temperature: 0℃ to 40℃(32°F to 104°F)
Storage Temperature: -20℃ to 85℃(-4°F to 185°F)
Environmental Working Humidity: 20%~90%RH
Storage Humidity: 5%-95%RH

FAQ

A. Why is there no audio output from HDMI ?
1. Pls make sure if there's audio output on the Monitor.
2. Pls set the external monitor as default audio output device.
B. What if the WIFI drops when the hard drive has been connected to the hub ?
1. 2.4G is easily interfered, you can switch to 5G network, or try to move the hard drive to a suitable place.
C. What if the USB driver can't be identified ?
1. Restart the device and connect the hub again.
D. What if the display screen drops after connecting a large current hard drive ?
1. Pls supply power by power adapter always.

Computer Model support DP1.4 signal	Remark
Macbook pro2018（15.4"）	The computers supporting DP1.4 signal output depends on the specifications of computer and graphics card This product only support 4K 60Hz for these specifications of computers. The output bandwidth of DP1.2 signal is not enough to output 4K 60Hz, only available for 4K 30Hz. If you have questions about the specifications of your computer,you can check the computer information and consult professional personnel
Macbook pro2019（15.4"）	
Macbook pro2019（16"）	
Macbook Air2020（13）	
IPAD pro 2018/2020	
Surface Laptop3	
Surface Pro7	
DELL XPS 9300	
DELL XPS 9370	
HP Spectre X360	
HP ENVY X360	
HP EliteBook 745 G5	
The above list is not exhaustive (the above list does not represent the whole)， more models will be updated regularly.	

Made in China