RLN16-410-4K-PoE-NVR-Specifications		
	Model	**RLN16-410**
Hardware	Hardware	3TB HDD: H3MB18/N6MB01 4TB HDD: N6MB01
Video/Audio Input	IP Video Input	PoE IP camera x 16
	Audio Input	Cameras with built-in mic
Video/Audio Output	Video Output	VGA, HDMI
	Display Resolution	HDMI: 3840*2160, 1920*1080, 1280*1024, 1280*720, 1024*768
		VGA: 1920*1080, 1280*1024, 1280*720, 1024*768
	Audio output	1-channel, RCA
Decoding	Live View / Playback Resolution	4096*3072/3840*2160/2560*1920/2560*1440/2048*1536/2304*1296/1080p/720p
	Video Format	H.265, H.264
	Synchronous Playback	Up to 4 channels
HDD	SATA	2 x SATA interface (1 x 3TB/4TB HDD included)
	Capacity	Up to 12TB (max. 6TB capacity for each HDD)
	External HDD	No
External Interface	USB Interface	2 x USB 2.0
	Network Interface	1, RJ-45 10/100/1000 Mbps self-adaptive Ethernet interface for LAN/WAN
		16, RJ-45 10/100 Mbps self-adaptive PoE Ethernet interface for IP camera
PoE	Max. Power Per Port	25W
	Supported Standard	IEEE 802.3 af/at
Network	Network Protocol	HTTP, TCP/IP, UDP, DHCP, P2P, UPNP, RTSP, SMTP, SSL/TLS, DNS, DDNS, NTP, FTP
	Browser Supported	Firefox, Chrome, Edge, Safari
	OS Supported	PC: Windows, Mac OS; smartphone: iOS, Android
	Max. User Access	20 users (1 admin account & 19 user accounts); up to 12 simultaneous video streams (10 substreams & 2 mainstreams)
General	Power Supply	DC 48V~54V
	Power Consumption	<10W (without HDD & PoE)
	Working Environment	Temperature: -10°C~+45°C (14°F~113°F); humidity: 10%~90%
	Dimensions	330 x 45 x 285mm
	Weight	2.4kg
Warranty	Limited Warranty	2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/.