ELECTROMAGNETIC EMISSIONS COMPLIANCE REPORT
FCC PART 15 SUBPART C REQUIREMENT

OF

Smart LED Strip Light

Model No.: ZC05M, ZC03M, ZC05M-USB, ZC05M-3, ZC05M-5, ZC05M-10, ZC05M-20, GD-CW02, GD-CW03, GD-CW03-5, GD-CW03-10, GD-CW03-20

Trademark: GIDEALED

FCC ID: 2A5TGZC05M

Report No.: E01A22020346F00201

Issue Date: Mar. 31, 2022

Prepared for

Jiang men shi jiwei ke ji you xian gong si

Room 706, No. 61, Donghua 1st Road, Pengjiang District, Jiangmen City, Guangdong Province, China

Prepared by

Dong Guan Anci Electronic Technology Co., Ltd.

1-2 Floor, Building A, No.11, Headquarters 2 Road, Songshan, Lake Hi-tech Industrial Development Zone, Dongguan City, Guangdong Pr., China.

This report shall not be reproduced, except in full, without the written approval of Dong Guan Anci Electronic Technology Co., Ltd.

VERIFICATION OF COMPLIANCE

Applicant:	Jiang men shi jiwei ke ji you xian gong si Room 706, No. 61, Donghua 1st Road, Pengjiang District, Jiangmen City, Guangdong Province, China
Manufacturer:	Jiang men shi ji di zhao ming ke ji you xian gong si 5th Floor, Building 3, No. 1 Minghui Road, Jianghai District, Jiangmen City, Guangdong Province, China
Product Description:	Smart LED Strip Light
Trade Mark:	GIDEALED
Model Number:	ZC05M, ZC03M, ZC05M-USB, ZC05M-3, ZC05M-5, ZC05M-10, ZC05M-20, GD-CW02, GD-CW03, GD-CW03-5, GD-CW03-10, GD-CW03-20 (All models have the same controller, different strip lengths and number of beads, we choose the max power model:ZC05M for all tests.)

We hereby certify that:

The above equipment was tested by Dong Guan Anci Electronic Technology Co., Ltd. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10-2013 and the energy emitted by the sample EUT tested as described in this report is in compliance with conducted and radiated emission limits of FCC Rules Part 15.247(2021).

Date of Test : Mar. 15, 2022 to Mar. 22, 2022

Prepared by : Tomas Yang/Editor

Approved & Authorized Signer : Alan He/Manager

Modified Information

Version	Summary	Revision Date	Report No.
Ver.1.0	Original Report	/	E01A22020346F00201

Table of Contents

1. GENERAL INFORMATION 6

1.1 PRODUCT DESCRIPTION 6
1.2 TEST METHODOLOGY 6

2. TEST FACILITY 7

3. DESCRIPTION OF TEST MODES 8

4. SUMMARY OF TEST RESULTS 10

5. TEST SYSTEM UNCERTAINTY 11

6. CONDUCTED EMISSIONS TEST 12

6.1MEASUREMENT PROCEDURE: 12
6.2TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 12
6.3MEASUREMENT EQUIPMENT USED: 12
6.4 CONDUCTED EMISSION LIMIT 12
6.5 MEASUREMENT RESULT: 13
6.5 CONDUCTED MEASUREMENT PHOTOS: 15

7. RADIATED EMISSION TEST 16

7.1MEASUREMENT PROCEDURE 16
7.2TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 18
7.3MEASUREMENT EQUIPMENT USED: 19
7.4 RADIATED EMISSION LIMIT 20
7.5 MEASUREMENT RESULT 21
7.6 RADIATED MEASUREMENT PHOTOS: 26

8. 6DB BANDWIDTH MEASUREMENT 27

8.1MEASUREMENT PROCEDURE 27
8.2TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 27
8.3 MEASUREMENT EQUIPMENT USED: 27
8.4 LIMIT 27
8.5MEASUREMENT RESULTS: 27

9. MAXIMUM PEAK OUTPUT POWER TEST 30

9.1MEASUREMENT PROCEDURE 30
9.2TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 30
9.3 MEASUREMENT EQUIPMENT USED: 30
9.4 PEAK POWER OUTPUT LIMIT 30
9.5 MEASUREMENT RESULTS: 30

10. POWER SPECTRAL DENSITY MEASUREMENT 32

10.1MEASUREMENT PROCEDURE 32

10.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 32
10.3 MEASUREMENT EQUIPMENT USED: 32
10.4 MEASUREMENT PROCEDURE 32
10.5 MEASUREMENT RESULTS: 33
11. BAND EDGE TEST 36
11.1 MEASUREMENT PROCEDURE 36
11.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 37
11.3 MEASUREMENT EQUIPMENT USED: 37
11.4 MEASUREMENT RESULTS: 38
12. ANTENNA PORT EMISSION 41
12.1 TEST EQUIPMENT 41
12.2 MEASURING INSTRUMENTS AND SETTING 41
12.3 TEST PROCEDURES 41
12.4 BLOCK DIAGRAM OF TEST SETUP 41
12.5 TEST RESULT 41
13. ANTENNA APPLICATION 44
13.1 ANTENNA REQUIREMENT 44
13.2 RESULT 44
14. PHOTOS OF EUT 45

1. GENERAL INFORMATION

1.1 Product Description

Characteristics	Description
Product Name	Smart LED Strip Light
Model number	ZC05M
Input Rating	DC 12V from adapter
Adapter Information	Model: CW1202000US Input: 100-240V~50/60Hz Output: DC 12V, 2A
Power Supply	AC 120V/60Hz for adapter
Modulation	O-QPSK
Operating Frequency Range	2405-2480MHz
Number of Channels	16
Channel Space	5MHz
Transmit Power Max(PK)	7.82dBm(0.0061W)
Antenna Type	PCB antenna
Antenna Gain	0 dBi

1.2 Test Methodology

All the test program has follow FCC new test procedure KDB 558074 D01 DTS Meas Guidance v05 and in accordance with the procedures given in ANSI C63.10-2013.

2. Test Facility

Site Description

EMC Lab.	:	Accredited by CNAS, 2017.06.26 The certificate is valid until 2022.10.28 The Laboratory has been assessed and proved to be in compliance with CNAS-CL01:2006 (identical to ISO/IEC 17025:2005) The Certificate Registration Number is L6214. Accredited by A2LA, 2018.03.15 The Certificate Number is 4422.01.
Name of Firm	:	Dong Guan Anci Electronic Technology Co., Ltd.
Site Location	:	1-2 Floor, Building A, No.11, Headquarters 2 Road, Songshan, Lake Hi-tech Industrial Development Zone, Dongguan City, Guangdong Pr., China.


3. Description of test modes

The EUT has been tested under its typical operating condition and fully-charged battery for EUT tested alone. Pre-defined engineering program for regulatory testing used to control the EUT for staying in continuous transmitting. Only the worst case data were reported.

The EUT has been associated with peripherals pursuant to ANSI C63.10-2013 and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: radiation (9 KHz to the 10th harmonics of the highest fundamental frequency or to 40 GHz, whichever is lower).

Pre-defined engineering program for regulatory testing used to control the EUT for staying in continuous transmitting mode is programmed. EUT is connected by com port, and transimit the control instruction via test software((SSCOM 3.2.exe).

Configuration of Tested System



Equipment Used in Tested System

Item	Equipment	Trademark	Model No.	FCC ID	Note
1.	Smart LED Strip Light	GIDEALED	ZC05M	2A5TGZC05M	***EUT***
2.	Adapter	Cenwell	Model: CW1202000US Input: 100-240V~50/60Hz Output: DC 12V, 2A	N/A	***Support Equipment***

The EUT has been tested under TX operating condition.

Channel List:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
11	2405	17	2435	23	2465
12	2410	18	2440	24	2470
13	2415	19	2445	25	2475
14	2420	20	2450	26	2480
15	2425	21	2455		
16	2430	22	2460		

Note:Test of channel was included the lowest 2405MHz, middle 2440MHz and highest frequency 2480MHz in highest data rate and to perform the test, then record on this report.

4. Summary of Test Results

FCC Rules	Description Of Test	Result
§15.207	AC Power Conducted Emission	Compliant
§15.247(d),§15.209	Radiated Emission	Compliant
§15.247(a)(2)	6dB Bandwidth Measurement	Compliant
§15.247(b)	MAXIMUM PEAK OUTPUT POWER TEST	Compliant
§15.247(e)	Power Spectral Density Measurement	Compliant
§15.247(d)	Band EDGE test	Compliant
§15.203	Antenna Requirement	Compliant
Remark: According to FCC OET KDB 558074, the report use radiated measurements in the restricted frequency bands. In addition, the radiated test is also performed to ensure the emissions emanating from the device cabinet also comply with the applicable limits.		

5. TEST SYSTEM UNCERTAINTY

The following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Parameter	Uncertainty
Radio Frequency	±1x10^-5
Maximum Peak Output Power Test	±1.0dB
Conducted Emissions Test	±2.0dB
Radiated Emission Test	±2.0dB
Power Density	±2.0dB
Occupied Bandwidth Test	±1.0dB
Band Edge Test	±3dB
All emission, radiated	±3dB
Antenna Port Emission	±3dB
Temperature	±0.5℃
Humidity	±3%


Remark: The coverage Factor (k=2), and measurement Uncertainty for a level of Confidence of 95%

6. Conducted Emissions Test

6.1 Measurement Procedure:

1. The EUT was placed on a table, which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured was complete.

6.2 Test SET-UP (Block Diagram of Configuration)



6.3 Measurement Equipment Used:

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	Calibrated until
L.I.S.N	SCHWARZBECK	NSLK 8127	8127-669	2022-05-22
10 db attenuator	JFW	50FP-010-H4	4360846-427-1	2022-05-22
RF Cable	N/A	N/A	2#	2022-05-22
EMI Test Receiver	ROHDE&SCHWARZ	ESCI	101358	2022-05-22

6.4 Conducted Emission Limit


(7) Conducted Emission

Frequency(MHz)	Quasi-peak	Average
0.15-0.5	66-56	56-46
0.5-5.0	56	46
5.0-30.0	60	50

Note:

1. The lower limit shall apply at the transition frequencies
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.


6.5 Measurement Result:



Site:	**843**	**Phase:L1**	**Temperature(C):26(C)**
Limit:	**FCC Part 15 C Conduction(QP)**		**Humidity(%):60%**
EUT:	**Smart LED Strip Light**	**Test Time:**	**2022-03-16**
M/N.:	**ZC05M**	**Power Rating:**	**AC 120V/60Hz**
Mode:	**Zigbee mode**	**Test Engineer:**	**Jack**
Note:			

No.	Frequency (MHz)	Reading Level(dBuV)	Factor (dB)	Measure-ment(dBuV)	Limit (dBuV)	Over (dB)	Detector	Comment
1	0.1620	38.42	10.16	48.58	65.36	-16.78	QP	
2	0.1620	24.71	10.16	34.87	55.36	-20.49	AVG	
3	0.2020	37.54	10.21	47.75	63.52	-15.77	QP	
4	0.2020	25.32	10.21	35.53	53.52	-17.99	AVG	
5	0.2660	34.49	10.20	44.69	61.24	-16.55	QP	
6 *	0.2660	26.30	10.20	36.50	51.24	-14.74	AVG	
7	0.4900	26.78	10.18	36.96	56.17	-19.21	QP	
8	0.4900	14.76	10.18	24.94	46.17	-21.23	AVG	
9	0.8180	23.06	10.14	33.20	56.00	-22.80	QP	
10	0.8180	14.39	10.14	24.53	46.00	-21.47	AVG	
11	1.7340	20.20	10.16	30.36	56.00	-25.64	QP	
12	1.7340	13.47	10.16	23.63	46.00	-22.37	AVG	

*:Maximum data x:Over limit !:over margin




Site:	**843**	**Phase:N**	**Temperature(C):26(C)**
Limit:	**FCC Part 15 C Conduction(QP)**		**Humidity(%):60%**
EUT:	**Smart LED Strip Light**	**Test Time:**	**2022-03-16**
M/N.:	**ZC05M**	**Power Rating:**	**AC 120V/60Hz**
Mode:	**Zigbee mode**	**Test Engineer:**	**Jack**
Note:			

No.	Frequency (MHz)	Reading Level(dBuV)	Factor (dB)	Measure-ment(dBuV)	Limit (dBuV)	Over (dB)	Detector	Comment
1	0.1500	37.10	10.15	47.25	65.99	-18.74	QP	
2	0.1500	22.52	10.15	32.67	55.99	-23.32	AVG	
3	0.1620	37.74	10.16	47.90	65.36	-17.46	QP	
4	0.1620	24.18	10.16	34.34	55.36	-21.02	AVG	
5	0.1986	37.27	10.21	47.48	63.66	-16.18	QP	
6	0.1986	24.60	10.21	34.81	53.66	-18.85	AVG	
7	0.2819	35.28	10.20	45.48	60.76	-15.28	QP	
8 *	0.2819	26.56	10.20	36.76	50.76	-14.00	AVG	
9	0.4460	25.85	10.17	36.02	56.95	-20.93	QP	
10	0.4460	12.10	10.17	22.27	46.95	-24.68	AVG	
11	0.6780	20.46	10.14	30.60	56.00	-25.40	QP	
12	0.6780	11.65	10.14	21.79	46.00	-24.21	AVG	

*:Maximum data x:Over limit !:over margin

6.5 Conducted Measurement Photos:



7. Radiated Emission Test

7.1 Measurement Procedure

1. The testing follows the guidelines in ANSI C63.10-2013.
2. Below 1000MHz, The EUT was placed on a turn table which is 0.8m above ground plane. And above 1000MHz, The EUT was placed on a styrofoam table which is 1.5m above ground plane.
3. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
4. The EUT was arranged to its worst case and then tune the Antenna tower (From 1m to 4m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
5. For measurement below 1GHz, if the emission level of the EUT measured by the peak detector is 3dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
6. Final measurement (Above 1GHz): The frequency range will be divided into different sub ranges depending of the frequency range of the used horn antenna. The EMI Receiver set to peak and average mode and a resolution bandwidth of 1MHz. The measurement will be performed in horizontal and vertical polarization of the measuring antenna and while rotating the EUT in its vertical axis in the range of 0 degree to 360 degree in order to have the antenna inside the cone of radiation.
7. Test Procedure of measurement (For Above 1GHz):
   1) Monitor the frequency range at horizontal polarization and move the antenna over all sides of the EUT(if necessary move the EUT to another orthogonal axis).
   2) Change the antenna polarization and repeat 1) with vertical polarization.
   3) Make a hardcopy of the spectrum.
   4) Measure the frequency of the detected emissions with a lower span and resolution bandwidth to increase the accuracy and note the frequency value.
   5) Change the analyser mode to Clear/ Write and found the cone of emission.
   6) Rotate and move the EUT, so that the measuring distance can be enlarged to 3m and the antenna will be still inside the cone of emission.
   7) Measure the level of the detected frequency with the correct resolution bandwidth, with the antenna polarization and azimuth and the peak and average detector, which causes the maximum emission.
   8) Repeat steps 1) to 7) for the next antenna spot if the EUT is larger than the antenna beamwidth.

Use the following spectrum analyzer settings:

When spectrum scanned from 30MHz to 1GHz setting resolution bandwidth 120KHz and video bandwidth 300KHz:

EMI Test Receiver	Setting
Attenuation	Auto
RB	120KHz
VB	300KHz
Detector	QP
Trace	Max hold

When spectrum scanned above 1GHz setting resolution bandwidth 1MHz, video bandwidth 3MHz:

EMI Test Receiver	Setting
Attenuation	Auto
RB	1MHz
VB	3MHz
Detector	Peak
Trace	Max hold

When spectrum scanned above 1GHz setting resolution bandwidth 1MHz, video bandwidth 10Hz:

EMI Test Receiver	Setting
Attenuation	Auto
RB	1MHz
VB	10Hz
Detector	Average
Trace	Max hold

For Average Measurement:


VBW=10Hz, when duty cycle is no less than 98 percent.

VBW≥1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.


Band	Duty Cycle(%)	T(μ s)	1/T(KHz)	Average Correction Factor	VBW Setting
2405-2480	100	-	-	0	10Hz

7.2 Test SET-UP (Block Diagram of Configuration)


(A) Radiated Emission Test Set-Up, Frequency Below 30MHz



(B) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(C) Radiated Emission Test Set-Up, Frequency above 1000MHz



7.3 Measurement Equipment Used:

Item	Equipment	Manufacturer	Model No.	Serial No.	Calibrated until
1.	EMI Test Receiver	Rohde & Schwarz	ESPI	100502	2022-11-12
2.	Pre-Amplifier	HP	8447D	2727A06172	2022-05-22
3.	Bilog Antenna	Schwarzbeck	VULB9163	VULB9163-588	2022-05-22
4.	Loop Antenna	Schwarzbeck	FMZB 1516	1516-141	2022-11-12
5.	Spectrum Analyzer	Rohde & Schwarz	FSV40	US40240623	2022-11-12
6.	Low noise Amplifiers	A-INFO	LA1018N4009	J101313052400 1	2022-05-22
7.	Horn antenna	A-INFO	LB-10180-SF	J203109061212 3	2022-05-22
8.	Broadband RF Power Amplifier	AEROFLEX	AEROFLEX10 0KHz-40GHz	J101313052400 1	2022-11-12
9.	DRG Horm Antenna	A.H.SYSTEMS	SAS-574	J203109061212 3	2022-11-12
10.	RF Cable	Gigalink Microwave	ZT40-2.92J-2. 92J-2m	N/A	2022-11-12
11.	RF Cable	Gigalink Microwave	ZT40-2.92J-2. 92J-0.3m	N/A	2022-11-12
12.	RF Cable	N/A	N/A	6#	2022-05-22
13.	RF Cable	N/A	N/A	1-1#	2022-05-22
14.	RF Cable	N/A	N/A	1-2#	2022-05-22
15.	RF Cable	N/A	N/A	7#	2022-05-22
16.	3m Semi-anechoic Chamber	chengyu	9m*6m*6m	N/A	2022-05-22
17.	Test Software	Farad	EZ-EMC Ver:ANCI-3A1	N/A	N/A

7.4 Radiated emission limit

The emissions from an intentional radiator shall not exceed the field strength levels specified in the following table 15.209(a):

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

15.205 Restricted bands of operation

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
[1]0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	([2])

Remark : 1. Emission level in dBuV/m=20 log (uV/m)
2. Measurement was performed at an antenna to the closed point of EUT distance of meters.
3. Only spurious frequency is permitted to locate within the Restricted Bands specified in provision of ξ 15.205, and the emissions located in restricted bands also comply with 15.209 limit.

7.5 Measurement Result

Below 30MHz:

Operation Mode:	TX	Test Date :	2022-03-16
Frequency Range:	9KHz~30MHz	Temperature :	25℃
Test Result:	PASS	Humidity :	58 %
Measured Distance:	3m	Test By:	Best

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV/m)	Limit 3m (dBuV/m)	Over (dB)
--	--	--	--	--

Note: The low frequency, which started from 9KHz-30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

Below 1000MHz:

Pass.

The data of the mode (O-QPSK 2480MHz) are recorded in the following pages.



Site:	**843.3**	**Antenna::Horizontal**	**Temperature(C):26(C)**
Limit:	**FCC Part 15 C Conduction(QP)**		**Humidity(%):60%**
EUT:	**Smart LED Strip Light**	**Test Time:**	**2022-03-16**
M/N.:	**ZC05M**	**Power Rating:**	**AC 120V/60Hz**
Mode:	**TX2480**	**Test Engineer:**	**Bast**
Note:			

No.	Frequency (MHz)	Reading Level(dBuV)	Factor (dB)	Measure-ment(dBuV)	Limit (dBuV)	Over (dB)	Detector	Comment
1	90.5374	42.66	-13.48	29.18	40.00	-10.82	QP	
2	135.0319	42.43	-12.15	30.28	40.00	-9.72	QP	
3	190.4050	43.24	-11.56	31.68	40.00	-8.32	QP	
4	252.9482	43.28	-9.33	33.95	47.00	-13.05	QP	
5	280.0237	47.40	-8.27	39.13	47.00	-7.87	QP	
6 *	296.1836	48.33	-7.48	40.85	47.00	-6.15	QP	

*:Maximum data x:Over limit !:over margin



Site:	**843.3**	**Antenna::Vertical**	**Temperature(C):26(C)**
Limit:	**FCC Part 15 C Conduction(QP)**		**Humidity(%):60%**
EUT:	**Smart LED Strip Light**	**Test Time:**	**2022-03-16**
M/N.:	**ZC05M**	**Power Rating:**	**AC 120V/60Hz**
Mode:	**TX2480**	**Test Engineer:**	**Bast**
Note:			

No.	Frequency (MHz)	Reading Level(dBuV)	Factor (dB)	Measure-ment(dBuV)	Limit (dBuV)	Over (dB)	Detector	Comment
1	42.8998	37.88	-10.58	27.30	40.00	-12.70	QP	
2	50.0566	33.09	-9.83	23.26	40.00	-16.74	QP	
3	141.3298	38.54	-12.17	26.37	40.00	-13.63	QP	
4	265.6757	41.18	-8.89	32.29	47.00	-14.71	QP	
5 *	298.2681	42.87	-7.26	35.61	47.00	-11.39	QP	
6	360.4476	37.39	-5.25	32.14	47.00	-14.86	QP	

*:Maximum data x:Over limit !:over margin

Above 1000MHz~10th Harmonics:

All the modulation modes were tested the data are recorded in the following pages. The frequency range from 1GHz to 25GHz is investigated.

Operation Mode: TX2405 Test Date : 2022-03-16
Test Voltage: AC 120V/60Hz Test by: Bast

Freq.	Ant. Pol.	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
(MHz)	H/V	PK	AV	PK	AV	PK	AV
4810	V	63.85	43.54	74	54	-10.15	-10.46
7215	V	63.97	42.15	74	54	-10.03	-11.85
9620	V	62.15	43.05	74	54	-11.85	-10.95
12025	V	62.64	44.15	74	54	-11.36	-9.85
14430	V	63.05	40.36	74	54	-10.95	-13.64
16835	V	63.15	41.55	74	54	-10.85	-12.45
4810	H	62.78	42.19	74	54	-11.22	-11.81
7215	H	62.64	42.64	74	54	-11.36	-11.36
9620	H	61.45	42.87	74	54	-12.55	-11.13
12025	H	60.69	42.63	74	54	-13.31	-11.37
14430	H	60.12	41.45	74	54	-13.88	-12.55
16835	H	59.88	40.32	74	54	-14.12	-13.68

Operation Mode: TX2445 Test Date : 2022-03-16
Test Voltage: AC 120V/60Hz Test by: Bast

Freq.	Ant. Pol.	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
(MHz)	H/V	PK	AV	PK	AV	PK	AV
4890	V	64.15	44.12	74	54	-9.85	-9.88
7335	V	62.15	43.64	74	54	-11.85	-10.36
9780	V	62.35	43.15	74	54	-11.65	-10.85
12225	V	63.87	43.05	74	54	-10.13	-10.95
14670	V	63.46	43.19	74	54	-10.54	-10.81
17115	V	62.59	42.64	74	54	-11.41	-11.36
4890	H	63.05	42.54	74	54	-10.95	-11.46
7335	H	61.11	41.78	74	54	-12.89	-12.22
9780	H	62.15	41.97	74	54	-11.85	-12.03
12225	H	63.05	40.52	74	54	-10.95	-13.48
14670	H	61.59	40.69	74	54	-12.41	-13.31
17115	H	60.96	39.87	74	54	-13.04	-14.13

Operation Mode: TX2480 Test Date : 2022-03-16

Test Voltage: AC 120V/60Hz Test by: Bast


Freq.	Ant. Pol.	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
(MHz)	H/V	PK	AV	PK	AV	PK	AV
4960	V	63.88	44.87	74	54	-10.12	-9.13
7440	V	63.54	43.64	74	54	-10.46	-10.36
9920	V	63.12	42.15	74	54	-10.88	-11.85
12400	V	62.69	42.85	74	54	-11.31	-11.15
14880	V	62.36	43.05	74	54	-11.64	-10.95
17360	V	62.54	43.16	74	54	-11.46	-10.84
4960	H	64.42	42.57	74	54	-9.58	-11.43
7440	H	63.58	42.55	74	54	-10.42	-11.45
9920	H	62.49	41.77	74	54	-11.51	-12.23
12400	H	61.33	40.28	74	54	-12.67	-13.72
14880	H	61.39	38.95	74	54	-12.61	-15.05
17360	H	60.25	39.16	74	54	-13.75	-14.84

Other harmonics emissions are lower than 20dB below the allowable limit.

Note: (1) All Readings are Peak Value and AV.
(2) Emission Level= Reading Level+ Probe Factor +Cable Loss.
(3) The average measurement was not performed when the peak measured data under the limit of average detection.
(4) Measuring frequencies from 1GHz to 25GHz.

7.6 Radiated Measurement Photos:






8. 6dB Bandwidth Measurement

8.1 Measurement Procedure

The EUT was operating in Bluetooth mode or could be controlled its channel. Printed out the test result from the spectrum by hard copy function.

8.2 Test SET-UP (Block Diagram of Configuration)



8.3 Measurement Equipment Used:

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	CALIBRATED UNTIL
Spectrum Analyzer	Rohde & Schwarz	FSV40	US40240623	2022-11-12
Coaxial Cable	Gigalink Microwave	ZT40	19022092	2022-11-12
Antenna Connector	ARTHUR-YANG	2244-N1TG1	N/A	2022-11-12

Remark: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

8.4 Limit

The minimum 6dB bandwidth shall be at least 500kHz.


8.5 Measurement Results:

Refer to attached data chart.

Spectrum Detector:	PK	Test Date :	2022-03-22
Test By:	Best	Temperature :	24 ℃
Test Result:	PASS	Humidity :	53 %


Channel number	Channel frequency (MHz)	Measurement level (KHz)	Required Limit (KHz)
11	2405	1842	>500
18	2440	1648	>500
26	2480	1641	>500

6dB NVNT Zigbee 2405MHz Ant1




Date: 22.MAR.2022 16:50:07

6dB NVNT Zigbee 2440MHz Ant1



Date: 22.MAR.2022 17:19:46

6dB NVNT Zigbee 2480MHz Ant1



9. MAXIMUM PEAK OUTPUT POWER TEST

9.1 Measurement Procedure

a. The Transmitter output (antenna port) was connected to the spectrum Analyzer.
b. Turn on the EUT and then record the peak power value.
c. Repeat above procedures on all channels needed to be tested.

9.2 Test SET-UP (Block Diagram of Configuration)



9.3 Measurement Equipment Used:

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	CALIBRATED UNTIL
USB RF Power sensor	RadiPower	RPR3006W	17I00015SNO88	2022-11-12
RF Test Software	MAIWEI	MTS 8310	N/A	N/A
Antenna Connector	ARTHUR-YANG	2244-N1TG1	N/A	2022-11-12

Remark: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

9.4 Peak Power output limit

The maximum peak power shall be less 1Watt.

9.5 Measurement Results:

Refer to attached data chart.

Spectrum Detector:	PK	Test Date :	2022-03-22
Test By:	Best	Temperature :	24 ℃
Test Result:	PASS	Humidity :	53 %


Channel number	Channel Frequency (MHz)	Peak Power output(dBm)	Peak Power output(mW)	Peak Power Limit(mW)	Pass/Fail
11	2405	7.82	6.053	1000	PASS
18	2440	7.32	5.395	1000	PASS
26	2480	6.75	4.732	1000	PASS

10. Power Spectral Density Measurement

10.1Measurement Procedure

The EUT was operating in Bluetooth mode or could be controlled its channel. Printed out the test result from the spectrum by hard copy function.

10.2 Test SET-UP (Block Diagram of Configuration)



10.3 Measurement Equipment Used:

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	CALIBRATED UNTIL
Spectrum Analyzer	Rohde & Schwarz	FSV40	US40240623	2022-11-12
Coaxial Cable	Gigalink Microwave	ZT40	19022092	2022-11-12
Antenna Connector	ARTHUR-YANG	2244-N1TG1	N/A	2022-11-12

Remark: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

10.4 Measurement Procedure

10.4.1 The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.

10.4.2. Set to the maximum power setting and enable the EUT transmit continuously.

10.4.3. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)

10.4.4. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.

10.4.5. Measure and record the results in the test report.

10.4.6. The Measured power density (dBm)/ 100KHz is a reference level and used as 20dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

10.5 Measurement Results:

The following table is the setting of spectrum analyzer.

Spectrum analyzer	Setting
Attenuation	Auto
Span Frequency	Set the span to 1.5 times the DTS bandwidth.
RB	3KHz
VB	10KHz
Detector	Peak
Trace	Max hold
Sweep Time	Automatic


Refer to attached data chart.

Spectrum Detector:	PK	Test Date :	2022-03-22
Test By:	Best	Temperature :	24 ℃
Test Result:	PASS	Humidity :	53 %

Channel number	Channel frequency (MHz)	Measurement level (dBm)	Required Limit (dBm/3kHz)	Pass/Fail
		PSD/3kHz		
11	2405	-7.64	8	PASS
18	2440	-8.57	8	PASS
26	2480	-8.43	8	PASS


Note:
1. Measured power density(dBm) has offset with cable loss.
2. The measured power density(dBm)/100KHz is reference level and used as 20dBc down for Conducted Band Edges and Conducted Spurious Emission limit line.

PSD NVNT Zigbee 2405MHz Ant1




Date: 22.MAR.2022 16:50:48

PSD NVNT Zigbee 2440MHz Ant1



Date: 22.MAR.2022 16:53:58

PSD NVNT Zigbee 2480MHz Ant1



11. Band EDGE test

11.1 Measurement Procedure

For Conducted Test

1. The transmitter output is connected to a spectrum analyzer. The resolution bandwidth is set to 100KHz. The video bandwidth is set to 300KHz.
2. The spectrum from 30MHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels.

EMI Test Receiver	Setting
Attenuation	Auto
RBW	100KHz
VBW	300KHz
Detector	Peak
Trace	Max hold

For Radiated emission Test

The EUT was placed on a styrofoam table which is 1.5m above ground plane.

The measurement procedure at the ban edges was simplified by performing the measurement in just one plot. Both, the in-band-emission and the unwanted emission were be encompassed by the span. After trace stabilization, the maximum peak was be determined by a peak detector and the value was marked by an appropriate limit line. The second limit line, which is 20dB below the first, marks the limit for the emissions in the unrestricted band. A maximum-peak-detector marks the highest emission in the unrestricted band next to the band edge.

The measurements were performed at the lower end of the 2.4GHz band.

Use the following spectrum analyzer settings:

For Restricted Band, When spectrum scanned above 1GHz setting resolution bandwidth 1MHz, video bandwidth 3MHz:


EMI Test Receiver	Setting
Attenuation	Auto
RBW	1MHz
VBW	3MHz
Detector	Peak
Trace	Max hold

For Non-Restricted Band, When spectrum scanned above 1GHz setting resolution bandwidth 100KHz, video bandwidth 300KHz:


EMI Test Receiver	Setting
Attenuation	Auto
RBW	100KHz
VBW	300KHz
Detector	Peak
Trace	Max hold

11.2 Test SET-UP (Block Diagram of Configuration)

For Conducted Test



For Radiated emission Test



11.3 Measurement Equipment Used:

For Conducted Test

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	CALIBRATED UNTIL
Spectrum Analyzer	Rohde & Schwarz	FSV40	US40240623	2022-11-12
Coaxial Cable	Gigalink Microwave	ZT40	19022092	2022-11-12
Antenna Connector	ARTHUR-YANG	2244-N1TG1	N/A	2022-11-12

Remark: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

For Radiated emission Test

Item	Equipment	Manufacturer	Model No.	Serial No.	Calibrated Until
1	Signal Analyzer	Rohde & Schwarz	FSV40	US40240623	2022-11-12
2	Broadband RF Power Amplifier	AEROFLEX	AEROFLEX100KHz-40GHz	J1013130524001	2022-11-12
3	DRG Horm Antenna	A.H.SYSTEMS	SAS-574	J2031090612123	2022-11-12
4	RF Cable	Gigalink Microwave	ZT40-2.92J-2.92J-2m	N/A	2022-05-22
5	RF Cable	Gigalink Microwave	ZT40-2.92J-2.92J-0.3m	N/A	2022-05-22


11.4 Measurement Results:

Refer to attached data chart.

Spectrum Detector:	PK	Test Date :	2022-03-22
Test By:	Best	Temperature :	24 ℃
Test Result:	PASS	Humidity :	53 %


1. Conducted Test

Frequency (MHz)	Peak Power Output(dBm)	Emission(dBm)	Result of Band edge(dBc)	Band edge Limit(dBc)
2314.4	4	-41.48	45.48	>20dBc
2497.3	1.6	-42.73	44.33	>20dBc



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.40445 GHz	4.00 dBm		
M2		1	2.4 GHz	-43.69 dBm		
M3		1	2.39 GHz	-44.30 dBm		
M4		1	2.3144 GHz	-41.48 dBm		



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.47945 GHz	1.60 dBm		
M2		1	2.4835 GHz	-44.42 dBm		
M3		1	2.5 GHz	-46.36 dBm		
M4		1	2.4973 GHz	-42.73 dBm		

2. Radiated emission Test

Spectrum Detector:	PK/AV	Test Date :	2022-03-16
Test By:	Bast	Temperature :	24 ℃
Humidity :	65 %		

Freq.	Ant. Pol.	Reading Level(dBuV/m)		Correct Factor	Emission Level(dBuV/m)		Limit 3m(dBuV/m		Margin(dB)	
(MHz)	H/V	PK	AV	dB	PK	AV	PK	AV	PK	AV
<2400	H	87.54	67.53	-26.3	61.24	41.23	74	54	-12.76	-12.77
<2400	V	85.34	65.34	-26.1	59.24	39.24	74	54	-14.76	-14.76
>2483.5	H	88.71	69.14	-26.3	62.41	42.84	74	54	-11.59	-11.16
>2483.5	V	84.73	64.72	-26.1	58.63	38.62	74	54	-15.37	-15.38

12. Antenna Port Emission

12.1 Test Equipment

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	CALIBRATED UNTIL
Spectrum Analyzer	Rohde & Schwarz	FSV40	US40240623	2022-11-12
Coaxial Cable	Gigalink Microwave	ZT40	19022092	2022-11-12
Antenna Connector	ARTHUR-YANG	2244-N1TG1	N/A	2022-11-12

Remark: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

12.2 Measuring Instruments and Setting

The following table is the setting of spectrum analyzer.


Spectrum analyzer	Setting
Attenuation	Auto
RB	100kHz
VB	300kHz
Detector	Peak
Trace	Max hold

12.3 Test Procedures

The testing follows the Measurement Procedure of FCC KDB No. 558074 D01 15.247 Meas Guidance v05r02 .

The conducted spurious emissions were measured conducted using a spectrum analyzer at low, Middle, and high channels, the limit was determined by attenuation 20dB of the RF peak power output.

12.4 Block Diagram of Test setup




12.5 Test Result



PASS.

Please refer to following pages.



Tx. Spurious Zigbee 2405MHz Emission

Reference	Emission
	

Tx. Spurious Zigbee 2440MHz Emission

Reference	Emission
	

Tx. Spurious Zigbee 2480MHz Emission

Reference	Emission
	

13. Antenna Application

13.1 Antenna requirement


The EUT'S antenna is met the requirement of FCC part 15C section 15.203 and 15.247.

FCC part 15C section 15.247 requirements:
Systems operating in the 2405-2480MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum peak output power of the intentional radiator is reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

13.2 Result

The EUT'S antenna is an PCB antenna. The antenna's gain is 0dBi and meets the requirement.


14. Photos of EUT







◄Reset
IDEALED
ZigBee3.0 Wireless LED Controller
Model NO:ZC05M
Input Voltage:DC12-24V
Total Power:120W Max
Output Current:5A Max
ZigBee HUB Required
Output
Input
CE RoHS
IP20









----------The end of report----------